

SiOO:X Prewash Application instructions

Preparations

Remove any existing oil or paint by washing or sanding. A rotating brush attached to a high-pressure washer can be helpful. Rinse with water and allow the wood to dry thoroughly.

Cover furniture and objects made of glass or metal – the products are alkaline and can leave stains. Use protective gloves. Planed surfaces must be sanded with 60 grit paper prior to treatment.

Remember

Lowest temperature for use: 0°C. Wipe away spills on glass or metal immediately with a wet rag. SiOO:X Prewash is not intended to remove stubborn oil and paint.

Instructions

Mix with water in a 1:8 dilution for regular cleaning, or a 1:4 ratio for more heavily soiled areas.

Rinse the surface with water, apply the pre-wash with a brush and leave it on for 10 minutes. Scrub with a medium stiff decking brush, and rinse off with water.

When cleaning surfaces already treated with SiOO:X using SiOO:X Prewash, some of the SiOO:X Surface Protection is dissolved. Finish off with a coat of SiOO:X Surface Protection when the surface has dried.

For timber which has not previously been treated with SiOO:X apply the full 3 coat SiOO:X Wood Protector and Surface Protector system once the timber has dried.

Amount required

One litre of diluted liquid is enough for about 4-5 square metres, depending on the degree of dirt and dilution.